

Date: 14TH February 1996
Ref: TB48
Raised By: TC
Distributed to: General

(Rev. 11/00)

MEGAS STUDIO, QUARTZ, SOLITAIRE (MIDI), SOLO MIDI
MIDI MUTE SYSTEM TEST SET-UPS

These mixers share a common Midi mute system program. This provides for some test and factory default (clear) procedures. Note that the following is not applicable to PC midi, CP and CM mixers which use a different processor system.

TEST PATTERN

These are internally stored mute patterns for test purposes.

****Warning:** This will clear previously stored memories!

Press RECALL UP and SHIFT DOWN simultaneously to load test patterns to memory. After completing test, use clear memory and reset procedures below.

SELF TEST

This sequences the system automatically through a series of test patterns and tests the midi port. ****Warning:** This will clear previously stored memories!

1. Connect a midi cable from midi IN to midi OUT. (Quartz: use midi 4 out)
2. Press EXT.PATCH, CH/PATCH and SHIFT UP simultaneously. (On some mixers this will be SELECT INT-EXT, SELECT MIDI-PATCH and SHIFT UP). If the cable is not present or the ports do not work the system will not sequence and appear frozen.
3. To stop, turn off power then use clear memory and reset procedures below.

CLEAR MEMORY

This will completely clear all contents from system memory (factory default).

Press RECALL UP and STORE simultaneously.

RESET

This resets system from faulty operation and operating modes to factory default.

Press EXT.PATCH, CH/PATCH and DUMP simultaneously.

Also see Technical Bulletin 88 for Mute system fault finding notes